

Single Pack FR10G 220-240V 50/60Hz RSIR

Single pack code number: **195B4505**

| Position | Title | Code | Amount |
|----------|--|----------|--------|
| 1 | Compressor FR10G | 103G6890 | 1 |
| 2 | PTC starting device (220V, 250hm, 4.8mm) | 103N0021 | 1 |
| 3 | Protection screen for PTC | 103N0476 | 1 |
| 4 | Cord relief | 103N1010 | 1 |
| 5 | Cover | 103N2010 | 1 |
| 6 | Bolt joint for one compressor M6 ø16mm | 118-1917 | 1 |

Secop GmbH • Lise-Meitner-Straße 29 • 24941 Flensburg, Germany • Tel: +49 461 4941 0 • www.secop.com

Secop accepts no responsibility for possible errors in catalogs, brochures, and other printed material. Secop reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without subsequent changes being necessary to specifications already agreed. All trademarks in this material are the property of the respective companies. Secop and the Secop logotype are trademarks of Secop GmbH. All rights reserved.

EN 12900 Household (CECOMAF) 220V, 50Hz, fan cooling F₂

| | | | | | | | | | | | | | | | | | |
|--------------------|-----|-----|-----|------|------|-------|------|------|------|------|------|------|------|------|------|----|----|
| Evap. temp. in °C | -45 | -40 | -35 | -30 | -25 | -23.3 | -20 | -15 | -10 | -6.7 | -5 | 0 | 5 | 7.2 | 10 | 15 | 20 |
| Capacity in W | | | | 91.9 | 136 | 152 | 188 | 250 | 324 | 380 | 412 | 516 | 638 | 697 | 779 | | |
| Power cons. in W | | | | 155 | 179 | 188 | 205 | 234 | 265 | 286 | 296 | 329 | 362 | 376 | 394 | | |
| Current cons. in A | | | | 1.51 | 1.58 | 1.61 | 1.66 | 1.75 | 1.84 | 1.91 | 1.94 | 2.05 | 2.16 | 2.21 | 2.28 | | |
| COP in W/W | | | | 0.59 | 0.76 | 0.81 | 0.91 | 1.07 | 1.22 | 1.33 | 1.39 | 1.57 | 1.76 | 1.85 | 1.98 | | |

EN 12900 Household (CECOMAF) 220V, 60Hz, fan cooling F₂

| | | | | | | | | | | | | | | | | | |
|--------------------|-----|-----|-----|------|------|-------|------|------|------|------|----|---|---|-----|----|----|----|
| Evap. temp. in °C | -45 | -40 | -35 | -30 | -25 | -23.3 | -20 | -15 | -10 | -6.7 | -5 | 0 | 5 | 7.2 | 10 | 15 | 20 |
| Capacity in W | | | | 98.8 | 153 | 173 | 217 | 292 | 381 | | | | | | | | |
| Power cons. in W | | | | 163 | 194 | 206 | 230 | 270 | 314 | | | | | | | | |
| Current cons. in A | | | | 1.32 | 1.44 | 1.48 | 1.57 | 1.73 | 1.90 | | | | | | | | |
| COP in W/W | | | | 0.61 | 0.79 | 0.84 | 0.94 | 1.08 | 1.21 | | | | | | | | |

ASHRAE LBP 220V, 50Hz, fan cooling F₂

| | | | | | | | | | | | | | | | | | |
|--------------------|-----|-----|-----|------|------|-------|------|------|------|------|------|------|------|------|------|----|----|
| Evap. temp. in °C | -45 | -40 | -35 | -30 | -25 | -23.3 | -20 | -15 | -10 | -6.7 | -5 | 0 | 5 | 7.2 | 10 | 15 | 20 |
| Capacity in W | | | | 113 | 167 | 188 | 232 | 308 | 400 | 470 | 510 | 639 | 791 | 866 | 968 | | |
| Power cons. in W | | | | 155 | 179 | 188 | 205 | 234 | 265 | 286 | 296 | 329 | 362 | 376 | 394 | | |
| Current cons. in A | | | | 1.51 | 1.58 | 1.61 | 1.66 | 1.75 | 1.84 | 1.91 | 1.94 | 2.05 | 2.16 | 2.21 | 2.28 | | |
| COP in W/W | | | | 0.73 | 0.93 | 1.00 | 1.13 | 1.32 | 1.51 | 1.65 | 1.72 | 1.94 | 2.19 | 2.30 | 2.46 | | |

ASHRAE LBP 220V, 60Hz, fan cooling F₂

| | | | | | | | | | | | | | | | | | |
|--------------------|-----|-----|-----|------|------|-------|------|------|------|------|----|---|---|-----|----|----|----|
| Evap. temp. in °C | -45 | -40 | -35 | -30 | -25 | -23.3 | -20 | -15 | -10 | -6.7 | -5 | 0 | 5 | 7.2 | 10 | 15 | 20 |
| Capacity in W | | | | 122 | 188 | 214 | 267 | 361 | 471 | | | | | | | | |
| Power cons. in W | | | | 163 | 194 | 206 | 230 | 270 | 314 | | | | | | | | |
| Current cons. in A | | | | 1.32 | 1.44 | 1.48 | 1.57 | 1.73 | 1.90 | | | | | | | | |
| COP in W/W | | | | 0.75 | 0.97 | 1.04 | 1.16 | 1.34 | 1.50 | | | | | | | | |



| Accessories for | FR10G | Figure | Code number |
|---------------------------|-------------------------|--------|-------------|
| PTC starting device | 6.3 mm spade connectors | a1 | 103N0011 |
| | 4.8 mm spade connectors | | 103N0018 |
| Starting relay | 6.3 mm spade connectors | a2 | 117U6010 |
| Start. capacitor 80 µF | 6.3 mm spade connectors | c | 117U5015 |
| Cover | | b | 103N2010 |
| Cord relief | | d | 103N1010 |
| Protection screen for PTC | | g | 103N0476 |

| Test conditions | EN 12900/CECOMAF | ASHRAE |
|-------------------------|------------------|--------|
| Condensing temperature | 55°C | 55°C |
| Ambient temperature | 32°C | 32°C |
| Suction gas temperature | 32°C | 32°C |
| Liquid temperature | 55°C | 32°C |

| Mounting accessories | | Code number |
|--------------------------|----------|-------------|
| Bolt joint for one comp. | Ø: 16 mm | 118-1917 |
| Bolt joint in quantities | Ø: 16 mm | 118-1918 |
| Snap-on in quantities | Ø: 16 mm | 118-1919 |

Secop accepts no responsibility for possible errors in catalogs, brochures, and other printed material. Secop reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without substantial changes being necessary to specifications already agreed. All trademarks in this material are the property of the respective companies. Secop and the Secop logotype are trademarks of Secop GmbH. All rights reserved. www.secop.com